CAMBRIDGE FIRE DEPARTMENT REGULATIONS FOR SPECIAL EVENTS WITH OUTDOOR COOKING

Effective November 1, 2008

- Maximum capacity of LP Gas allowed without a permit is 42 pounds.
- Maximum allowed size LP Gas cylinder for each cooking unit shall not exceed 42-pound capacity. NO spare cylinders are allowed and NO cylinder changes are allowed during the event. One cylinder on site per unit, per day only. No exceptions!
- Cooking units that require larger capacity cylinders for proper operation may be allowed provided, however, that the vendor obtains a permit from the fire department **prior** to the event.
- Prior to special events the Fire Department and an Inspectional Services Plumbing and Gas Inspector will inspect each cooking unit for compliance. Large-scale events may require additional requirements or restrictions.
- All cylinders must be properly secured so they cannot tip over or be easily accessed by the public. Cylinders must have quick fit disconnect fittings. Cylinders must be equipped with an OPD Over Pressurization Device. There are no exceptions to this provision!
- All cylinders must have a Massachusetts State Fire Marshal approved valve plug and legibly marked with approved DOT labels for LP Gas cylinders. Cylinders must be less than 12 years old.
- Each cooking unit must have a minimum of one, properly operating 20 B, C rated fire extinguisher within 5 feet of the unit. A current inspection tag must be attached.

- Charcoal cooking units must have a properly operating 2-½ gallon water extinguisher within 5 feet of the unit. (If possible a charged garden hose is also recommended)
- No cooking is allowed under tents. A tent may cover the unit from weather elements as long as it covers the unit only, and people do not have to go under the tent to procure food.
- No portable heaters are allowed under tents. If a tent must be heated, indirect heating may be allowed. For example, a force-fed hot air heating unit with an exterior power source.
- Mobile kitchens, catering vehicles and trailers must meet DOT and NFPA 58 standards.
- LP Gas cylinders shall be rejected if there is evidence of exposure to fire, bad gouges, dents or excessive corrosion. If there is suspicion of a leaking cylinder it will be shut down immediately.
- In closely crowded situations a separation must be maintained between vendors according to direction from the fire department.
- The storage of spare LP Gas cylinders in parked vehicles is forbidden. It is the responsibility of the vendor to bring a full cylinder to the event. Failure to properly plan does not absolve the vendor from compliance with these regulations.
- Generators may be powered only by diesel fuel or propane.
- All propane cylinders in use (cooking or generators) must have quick disconnect fittings.
- Failure to comply with these regulations will result in the shutting down and/or removal of the equipment from the event site.